

# ROOF BOLTER SAFETY

## Equipment Operation



- Never go in by roof supports.
- Always conduct a site examination and evaluation to identify any hazards or concerns.
- It takes teamwork— communicate all changing conditions, hazards and concerns to all your crew members.
- Promptly correct these hazards or concerns before starting to work in the area.
- Never take shortcuts.
- Avoid wearing loose fitting gloves or clothing that could be entangled in the machinery.
- Never operate machinery if it is not operating properly.
- Avoid pinch points, especially near the boom, ATRS and canopy.
- Always maintain safe body positioning between ribs and equipment.
- Avoid hand placement on rotating drill steels, booms and other moving components.
- Ensure ATRS is properly contacting the roof area.
- Keep other workers at a safe distance.



Rockwood Casualty Insurance Company (Rockwood) may provide safety management services to its insureds in order to reduce the risk of loss that may lead to insurance claims. The information and advice we provide is not intended to include all possible safety measures and controls. Rockwood does not warrant that losses and claims will be avoided or mitigated if our recommendations are followed. The safety management services we provide do not relieve the insured of its own duties and obligations with regard to safety matters, nor does Rockwood guarantee to the insured or others that the insured's property and/or operations are safe, healthful, or in compliance with applicable laws, regulations or standards. The insured remains responsible for its own operations, safety practices and procedures and should consult with legal counsel and safety professionals, of its own choosing, as it deems appropriate.